

## 6.0 Sport

Product Specifications	Standard	Result
Surface	X PUR scuff resistant surface	
Backing	Combined closed cell foam system	
Total Thickness	EN ISO 24346	6.0 mm
Width of roll	EN ISO 24341	2 m / 6.6 inches
Length of roll	EN ISO 24341	20 m, +/- 10%
Wear layer thickness	EN ISO 24340	0.9 mm
Weight		3250 g/m squared
Classification		
Product Specification	EN 14904, Vinyl Indoor sports floor (category P1)	
Impact sound insulation	EN ISO 717-2	21 dB
Thermal resistance		0.06 m squared K/W
Fire Resistance	EN 13501-1	
Sport Properties		
Fricton	EN 13036-4	80-110
Shock Absortion	EN 14808	≥ 25% (P1)
Vertical Deformation	EN 14809	1.0 mm
Ball Rebound	EN 12235	98%
Specular Gloss	EN 2813	< 30%
Technical		
Dimensional Stability	EN ISO 23999	+/- 0.2 %
Indentation resistance	EN 1516	<0.5 mm
Resistance to rolling load	EN 1569	1500 N
Colour Fastness	ISO 105 B02	6
Abrasion resistance	EN ISO 5470-1	<250 mg/1000 cycles
Chemical Resistance	EN ISO 26987	No change
Warranty		
15 year limited commercial wear warranty.		
Please visit <a href="http://www.FASmaterials.com">www.FASmaterials.com</a> for the most current warranty information.		