

# FAS | MATERIALS

## Extreme Purpose

Product Specifications	Standard	Result
<b>CONSTRUCTION</b>		
Total Thickness	EN ISO 24346	2.0 mm
Width of roll	EN ISO 24341	2 m / 6.6 inches
Length of roll	EN ISO 24341	20 lm
Wear layer thickness	EN ISO 24340	0.7 mm
Total weight		2.2 kg/m <sup>2</sup>
<b>Classification</b>		
European Classification	EN 685	Class: 33/43
<b>Performance</b>		
Dimensional Stability	EN ISO 23999	Max: 0.2 %
Light Fastness	EN 20105 B02	Grade 6
Abrasion Group	MSZ EN 660-1	Class: T
Fire Resistance	EN 13501-1, Gost 30402-94 DIN 4102/ONORM	Class: BFL-S1, G1 Class, B1 Class
Slip Resistance	DIN 51130 EN 13893	R9 DS Class
Electrical Resistance	EN1815 EN 1081	☒ 2 kV ≤ 10 <sup>9</sup> Ω
Residual Indentation	EN ISO 24343	Max. 0.1 mm
Chemical Resistance	EN ISO 26987	✓
Castor Chair Resistance	EN ISO 4918	✓
Environmental Attributes		Phthalate-free product
Anti-bacterial and fungicid treatment		graboSAN
Bacteria resistance	EN ISO 846:1999	✓
Antimicrobial activity	ISO 27447	☒ 99%
Seaming method		Heat or cold weld
<b>Warranty</b>		
15 year limited commercial wear warranty.		
Please visit <a href="http://www.FASmaterials.com">www.FASmaterials.com</a> for the most current warranty information.		