

FAS | MATERIALS

Heavy Duty LVT

Product Specifications		
CONSTRUCTION	Luxury Vinyl Tile with iGuard Surface	
PLANK SIZE	EN ISO 24346	7.25" by 28"
THICKNESS	EN ISO 24346	3 mm
WEAR LAYER	EN ISO 24340	40 mil
TOTAL WEIGHT	EN ISO 23997	4.6 KG/M ²
Classification		
Binder Content	EN ISO 10582	Type I
European Classification	EN ISO 10582	Class: 33/43
Residual Indentation	EN ISO 24343	Max. 0.1 mm
Dimensional Stability	EN ISO 23999	Max: 0.25
Curling	EN ISO 23999	Max. 2 mm
Performance		
Abrasion Group	MSZ EN 660-1	Class: T
Fire Resistance	EN 13502-1	Class: BFL-S1
Slip Resistance	EN 13893	DS
Electrical Properties	EN 1815	Max. 2KV / Antistatic
Light Fastness	EN ISO 105-B0	Grade 6
Chemical Resistance	EN ISO 26987, ASTM F925	Yes, Yes
Hygiene	Bacterial Resistant	
Castor Chair Resistance	EN 425 / ISO 4918	Yes
Environmental Attributes	Solvent and Phtalathe Free	
Surface Treatment	iGuard PUR Surface / Easy Cleaning	
Content of PCP	EN 12673	Does not contain
Formaldehyde Emission	ENV 717-1	E1 (no emission)
VOG		Pass
CE Marking	EN 14041	Yes
Warranty		
20 year limited commercial wear warranty.		
Please visit www.FASmaterials.com for the most current warranty information.		