

Paramount

Product Specifications	Standard	Result
CONSTRUCTION		
CONSTRUCTION		Non-direction Homogeneous sheet flooring
Total Thickness	EN ISO 24346	2.0 mm
Width of roll	EN ISO 24346	2 m / 6.6 inches
Length of roll	EN ISO 24340	20 lm
Wear layer thickness	EN ISO 23997	2.0 mm
Total weight		2.8 kg/m2
Classification		
Binder Content	EN ISO 10581	Class: Type I
European Classification	ISO 10874	Class: 33/43
Residual Indentation	EN ISO 24343-1	Max. 0.1 mm
Dimensional Stability	EN ISO 23999 EN ISO 23999	Max: 0.2 %, Ave: 0.1 %
Curling	EN ISO 23999	Max. 8 mm
Performance		
Abrasion Group	MSZ EN 660-1	Class: T
Fire Resistance	EN 13501-1	Class: BFL-S1
Slip Resistance	DIN 51130 EN 13893	R9 DS
Thermal resistance	m2K/W	0.012
Light Fastness	EN ISO 105-B02	Grade 6
Chemical Resistance	EN ISO 26987, ASTM F925	✓ ✓
Hygiene		Bacterial Resistant
Castor Chair Resistance	ISO 4918	✓
Environmental Atributes		Phthalate-, solvent and heavy metal free
Surface Treatment		iGuard PUR Surface
Content of PCP	EN 12673	Does not contain
Formaldehyde Emission	ENV 717-1	E1 (no emission)
Seaming method		Heat or cold weld
CE Marking	EN 14041	✓
Warranty		
10 year limited commercial wear warranty.		
Please visit www.FASmaterials.com for the most current warranty information.		