FAS MATERIALS

Quiet SPC Click Plank

_			_		
Р	roc	luct	Spe	2011108	ations

Style Name Quiet SPC Click Plank

Style Number All Wood

Construction Heavy Commercial VTB Core

Class I Printed Film Vinyl Tile, Type A (smooth), Type B

Class / ASTM F 1700 (embossed)

Wear layer Thickness 20 mil or (0.5mm)

Overall Thickness 5.5 mm

Nominal Dimensions Plank 7.25" wide x 48" long

Actual Size / ASTM F 536 Width: 7.25" or 184.15mm, Length: 48" or 1219.2mm

Backing Class Recycled Commercial Grade EVA
Finish GlobalTECH-Enhanced Urethane

Added Antimicrobial Yes
Installation Floating
Recommended Adhesive N/A

Packaging

Square Feet per carton 23.51 SF planl
Pieces per carton 10 pcs plank
Weight per carton 40 lbs.

Testing

Slip Resistance / ASTM D 2047 >0.80

Residual Indentation / ASTM F970 2200 psi
Flexibility / ASTM F 137 Passes

Resistance to Heat / ASTM F 1514 Passes

Resistance to Light / ASTM F 925 Passes

Radiant Flux / ASTM 648 Passes, >0.45 watts/cm2, NFPA Class I

Smoke Density / ASTM E 662 Passes, <450

Warranty

10 year limited commercial wear warranty.

Please visit www.FASmaterials.com for the most current warranty information.

Environmental

Indoor Air Quality FloorScore certified LEED Scorecard MR4, IEQ4.1, IEQ4.3