

Silver Protection Sheet

Product Specifications	Standard	Result
CONSTRUCTION		
CONSTRUCTION		Compact Heterogeneous
Total Thickness	EN 428	2.0 mm
Width of roll	EN 426	2 m / 6.6 inches
Length of roll	EN 426	20 lm
Wear layer thickness	EN 429	0.7 mm
Total weight		2.8 kg/m ²
Classification		
Product Specification	EN 649	✓
European Classification	EN 685	Class: 33/43
Residual Indentation	EN 433	Max. 0.1 mm
Dimensional Stability	EN 434	Max: 0.2 %
Light Fastness	EN 20105 B02	Grade 6
Performance		
Abrasion Group	MSZ EN 660-1	Class: T
Fire Resistance	EN 13501-1, Gost 30402-94	Class: BFL-S1, G1
Slip Resistance	DIN 51130 ASTM D2047-99	R10 Dry: 0.88 / Wet: 0.86
Electrical Resistance	EN1815 EN 1081	☒ 2 kV ≤ 10 ⁹ Ω
Chemical Resistance	EN 423, ASTM F925-02	✓ ✓
CE Marking	EN 14041	✓
Castor Chair Resistance	EN 425	✓
Environmental Atributes		Phthalate-free product
Surface Treatment		TECH Surface
Anti-bacterial and fungicid treatment		SilverKnight
Bacteria resistance	EN ISO 846:1999	✓
Antimicrobial activity	ISO 27447	☒ 99%
Seaming method		Heat or cold weld
VOC	Floor Score	✓
Warranty		
15 year limited commercial wear warranty.		
Please visit www.FASmaterials.com for the most current warranty information.		